



NO. 8 CRUSHED AND WASHED AGGREGATE IN OPENINGS

STONEBILT CONCEPTS PAYER SLAB, 1 3/4" THICK

CURB/EDGE RESTRAINT WITH CUT-OUTS FOR OVERFLOW DRAINAGE (CURB SHOWN)

BEDDING COURSE: 1-1/2" TO 2" THICK, NO. 8 GRAVEL, CRUSHED AND WASHED

BASE COURSE: 4" THICK, NO. 57 STONE, CRUSHED AND WASHED OPEN-GRADED BASE

SUBBASE COURSE: 6" THICK, NO. 2 STONE CRUSHED AND WASHED

OPTIONAL GEOTEXTILE ON BOTTOM AND SIDES OF SUBBASE, BASE AND BEDDING COURSES

PERFORATED PIPES SPACED AND SLOPED TO DRAIN ALL STORED WATER

OUTFALL PIPE(S) SLOPED TO STORM SEWER OR STREAM

SOIL SUBGRADE SLOPED TO DRAIN

**NOTES:**

1. PEDESTRIAN APPLICATIONS ONLY.
2. NO. 2 STONE SUBBASE THICKNESS VARIES WITH DESIGN AS PER GEOTECH REPORT.

**PERMEABLE PAVEMENT WITH PARTIAL EXFILTRATION TO SOIL SUBGRADE**

STONEBILT CONCEPTS  
STANDARD DRAWING  
2009  
NOT TO SCALE

9455 BOSTON COURT  
HENDERSON, CO 80640  
303-867-6700

